

A COMPLETE WATERING DESIGN YOU CAN SEE & TRUST



THE EASIEST WAY TO CARE FOR AND MAINTAIN YOUR BATTERIES

Gravity Fill System



Manual Pump



Direct Fill Link



WATER DELIVERY OPTIONS

Gravity Fill System is ideal for a small number of batteries when a water source is not readily available. The 2.5 gallon gravity fill tank should be placed at least three feet above the battery tops to ensure sufficient water flow.

The Direct Fill Link features a built-in flow indicator and pressure regulator. The pressure sensitive handle reduces pressure down to 10 psi and will handle incoming pressure up to 100 psi.

It connects directly to a clean* water source.

*See water purity recommendations

MADE IN THE USA
DISTRIBUTED WORLDWIDE
BY



Battery Watering Technologies

SINGLE POINT WATERING SYSTEM

(800) 695-0945
fx. 951-371-4671
WWW.USBATTERY.COM

Sense Smart Valve

Innovative Valve Designs



The ONLY valve with an electrolyte sensor built-in

AVAILABLE IN TWO MODELS:

TBU 1000

TBU 2000 (INCLUDES A 6'

DASHBOARD MOUNTABLE LED INDICATOR)

Designed Exclusively for U.S. Battery Products

LOW PROFILE DESIGN

REDUCES RISK OF DAMAGE FROM BATTERY CABLES

ELECTROLYTE LEVEL INDICATOR EYE

VISIBLE FROM TOP AND SIDE

CLIP-IN BASE

INSTALLATION IS FAST AND EASY WITH NO TWISTING TO LOCK IN PLACE

SOLID ONE PIECE FLOAT

ACID, TEMPERATURE AND IMPACT RESISTANT; SOLID CONSTRUCTION CANNOT ABSORB WATER

PROTECTIVE SHROUD

EASY TO USE

WATER FLOWS THROUGH A SINGLE CONNECTION REDUCING LABOR COST BY ACCURATELY FILLING EACH BATTERY SET IN LESS THAN 30 SECONDS! INNOVATIVE CLIP-IN VALVE MAKES INSTALLATION OF PRE-STRUNG SYSTEMS FAST AND EASY.

LED Indicator tells you when it is time to add water to batteries.



Electrolyte level is OK



Water is needed

SAFE

THE SPARK ARRESTOR MAKES THIS THE SAFEST WATERING SYSTEM AVAILABLE.

model VB-TBU

WWW.USBATTERY.COM