


XC™ **FEATURES:**

- XC** **Highest** initial capacity.
- XC** **Highest** total energy delivered over the life of the battery.
- XC** **Fastest** cycle up to full rated capacity.



1675 Sampson Ave.
Corona, CA 92879
951.371.8090

1895 Tobacco Rd.
Augusta, Georgia 30906
706.790.0218

717 North Belair Road
Evans, Georgia 30809
706.868.0533

DEEP CYCLE BATTERIES

US BATTERY MODEL	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	M.C.A. @ 32° F	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
						LENGTH	WIDTH	HEIGHT		

6 VOLT GOLF CAR & MULTI PURPOSE

US 1800XC2	208	157	-	107	392	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 2000XC2	220	172	-	115	445	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 2200XC2	232	181	-	122	474	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 125XC2	242	198	-	140	517	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 145XC2	251	213	-	154	562	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48

8 VOLT GOLF CAR & MULTI PURPOSE

Min. @ 56 Amps										
US 8VGCXC2	155	129	110	75	312	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 8VGCXC2	170	133	118	82	325	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VGCXCXC2	183	147	136	95	365	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VHATBXC2	205	170	164	115	435	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48

6 VOLT GOLF, SWEEPER/SCRUBBER & MULTI PURPOSE

US 250XC2	255	217	-	159	570	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 250HCXC2	280	239	-	178	635	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 305XC2	290	245	-	182	660	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	BLK/BLK	18
US 305XC2	310	261	-	195	715	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US 305HCXC2	340	283	-	215	790	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US L16EXC2	360	270	-	198	795	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	BLK/BLK	18
US L16XC2	385	297	-	225	865	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US L16HCXC2	420	323	-	250	965	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US 1 HCXC2	95	-	-	44	165	8 3/4 (222)	6 7/8 (175)	9 (175)	BLK/BLK	72
US 100DINXC2	247	199	-	135	560	9 5/8 (244)	7 1/2 (191)	10 7/8 (276)	RED/RED	48

12 VOLT GOLF, SWEEPER/SCRUBBER & MULTI PURPOSE

US 12VRXXC2	155	122	-	77	292	14 (355) w/ handles	7 1/16 (179)	11 3/8 (289)	RED/RED	36
US 12VEXC2	145	115	-	62	270	14 (355) w/ handles	7 1/16 (179)	11 3/8 (289)	BLK/BLK	36
US 185XC2	200	158	-	106	398	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185HCXC2	220	172	-	117	443	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185EXC2	185	144	-	93	355	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	BLK/BLK	14

8 VOLT MARINE

15-4-1 XC2	195	-	-	133	440	24 3/8 (619)	7 7/16 (189)	10 1/2 (267)	RUBBER	16
17-4-1 XC2	220	-	-	147	490	27 7/16 (698)	7 7/16 (189)	10 1/2 (267)	RUBBER	16
19-4-1 XC2	245	-	-	162	545	26 3/4 (679)	8 7/16 (216)	11 1/8 (282)	RUBBER	16

12 VOLT SWEEPER/SCRUBBER, MARINE & MULTI PURPOSE

CCA @ 0°F										
US 24 DCXC2	85	68	400	38	145	10 7/8 (276)	6 3/4 (171)	9 3/8 (238)	RED/RED	72
US 27 DCXC2	105	89	575	54	205	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	RED/RED	54
US 31 DCXC2	130	99	620	59	225	13 (330)	6 3/4 (171)	9 5/8 (243)	RED/RED	54

12 VOLT MULTI PURPOSE

8D-HCXC2	240	177	-	115	470	20 3/4 (527)	11 1/8 (283)	9 7/8 (251)	BLK/BLK	16
----------	-----	-----	---	-----	-----	--------------	--------------	-------------	---------	----

6 VOLT RENEWABLE ENERGY

US RE L16XC2	401	317	-	245	915	11 7/8 (302)	7 7/8 (181)	16 3/4 (425)	GRN/GRN	18
US REGC2HXC2	242	194	-	136	507	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	GRN/GRN	48

2 VOLT RENEWABLE ENERGY

US RE L162VXC2	1100	962	-	845	2826	11 7/8 (302)	7 7/8 (181)	16 3/4 (425)	GRN/GRN	18
----------------	------	-----	---	-----	------	--------------	-------------	--------------	---------	----

LOW MAINTENANCE STARTING BATTERIES

BCI GROUP SIZE	US BATTERY MODEL	C.C.A. @ 0° F	C.A. @ 32° F	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
					LENGTH	WIDTH	HEIGHT		

6 VOLT AUTOMOTIVE & COMMERCIAL

2E	2E	600	730	180	19 3/8 (492)	4 1/8 (105)	9 1/8 (232)	RUBBER	60
19L	19L	525	640	110	8 3/16 (208)	6 11/16 (170)	7 7/16 (189)	RUBBER	90

12 VOLT TRUCK - BUS - COMMERCIAL

17TF	17TF	625	765	150	17 1/16 (433)	6 15/16 (176)	8 (203)	RUBBER	42
------	------	-----	-----	-----	---------------	---------------	---------	--------	----

12 VOLT MILITARY ORDINANCE

6TL(mil)	6TL	825	1010	215	10 1/2 (267)	11 7/8 (302)	9 (229)	OLV/OLV	32
----------	-----	-----	------	-----	--------------	--------------	---------	---------	----

12 VOLT GAS GOLF CAR & AUTOMOTIVE

53	53K-30	360	440	65	12 3/4 (324)	4 5/8 (117)	8 15/16 (227)	BLK/BLK	90
----	--------	-----	-----	----	--------------	-------------	---------------	---------	----



6,8,& 12 Volt AGM - Sealed Non-spillable Batteries

US BATTERY MODEL	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	M.C.A. @ 32° F	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
						LENGTH	WIDTH	HEIGHT		

6 VOLT SEALED AGM

US AGM 2000	213	182	855	124	475	10.24 (260)	7.09 (180)	10.79 (274)	GOLD	32
US AGM 6V27	214	172	1000	112	450	12.05 (306)	6.61 (168)	9.98 (228)	GOLD	24
US AGM 2224	224	175	855	120	450	10.24 (260)	7.09 (180)	10.79 (274)	GOLD	30
US AGM 250	260	212	895	149	572	11.61 (295)	7.09 (180)	11.73 (298)	GOLD	24
US AGM 305	312	273	865	208	736	11.61 (295)	7.09 (180)	14.41 (366)	GOLD	12
US AGM L16	390	326	875	255	915	11.61 (295)	7.09 (180)	16.85 (428)	GOLD	12

8 VOLT SEALED AGM

US AGM 8V170	170	152	---	108	375	10.24 (260)	7.09 (180)	10.79 (274)	GOLD	32
--------------	-----	-----	-----	-----	-----	-------------	------------	-------------	------	----

12 VOLT SEALED AGM

US AGM U1	32.3	29.8	280	13	51	7.68 (195)	5.12 (130)	7.09 (180)	GOLD	95
US AGM 27	99	82	900	52	185	12.05 (306)	6.61 (168)	9.06 (230)	GOLD	24
US AGM 31	100	85	960	52	190	13.7 (348)	6.85 (174)	9.37 (238)	GOLD	24
US AGM 12V150	150	129	---	86	310	12.97 (327)	7.09 (180)	10.8 (274)	GOLD	24
US AGM 185	234	191	930	125	518	15.24 (387)	7.09 (180)	14.49 (368)	GOLD	10