

# DEEP CYCLE AGM



INTRODUCING THE NEW AND IMPROVED  
**AGM DEEP CYCLE BATTERIES**



The Deep Cycle Battery Leader Since 1926

[WWW.USBATTERY.COM](http://WWW.USBATTERY.COM)

# TRUE DEEP CYCLE AGM BATTERIES!

U.S. Battery's new **AGM DEEP CYCLE** batteries include updated features such as the use of **THICK POSITIVE ALLOY GRIDS** for exceptional corrosion resistance, **HIGH-DENSITY POSITIVE ACTIVE MATERIAL**, and **ADVANCED GLASS MAT SEPARATORS**. These components work together to maintain the battery cell structure during deep-cycling, limit acid stratification, and inhibit internal shorts.

The batteries also feature a **CARBON-ENHANCED NEGATIVE ACTIVE MATERIAL** that improves charge acceptance and cycling performance. In addition to designed-in vibration resistance and maintenance-free valve-regulated operation, U.S. Battery's new AGM design improves reliability and overall performance and delivers longer cycle life. The sealed Maintenance-Free line is engineered to deliver a deep cycle cost effective alternative to Lithium batteries.

## 6 VOLT AGM

Model	BCI Group Size	Terminal	20 HR Rate	Minutes @75 AMPS	Minutes @25 AMPS	Length	Width	Height	Weight lbs. (kg)
US AGM 2000	GC2	Dual	210	120	460	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)	60 (27.2)
US AGM 2224	GC2	F14	224	135	490	10.2" (260mm)	7.09" (180mm)	9.9" (252mm)	69.4 (31.5)
US AGM 6V260	GC2	F14	260	156	560	10.2" (260mm)	7.09" (180mm)	10.7" (278mm)	75 (34)
US AGM 6V27	27	T11	215	112	500	12.05" (306mm)	6.61" (168mm)	8.98" (228mm)	64 (28.8)
US AGM 305	902	Dual	340	240	790	11.61" (295mm)	7" (178mm)	14.3" (364mm)	105.8 (48)
US AGM L16	903	Dual	414	275	984	11.61" (295mm)	7" (178mm)	16.65" (423mm)	126 (57)
US AGM DIN	DIN	F14	225	130	470	9.57" (243mm)	7.38" (187.5mm)	10.8" (275mm)	70.5 (32)

## 8 VOLT AGM

Model	BCI Group Size	Terminal	20 HR Rate	Minutes @56 AMPS	Minutes @25 AMPS	Length	Width	Height	Weight lbs. (kg)
US AGM 8V170	GC8	Dual	180	120	381	10.2" (260mm)	7.17" (182mm)	11.3" (286mm)	76 (34.5)

## 12 VOLT AGM

Model	BCI Group Size	Terminal	20 HR Rate	Minutes @75 AMPS	Minutes @25 AMPS	Length	Width	Height	Weight lbs. (kg)
US AGM U1	U1	F11	35	11	45	7.68" (195mm)	5.12" (130mm)	7.13" (181mm)	22 (9.8)
US AGM 24	24	Dual	90	43	175	10.24" (260mm)	6.61" (168mm)	8.43" (214mm)	52 (23.5)
US AGM 27	27	Dual	108	55	220	12.05" (306mm)	6.61" (168mm)	9.17" (233mm)	61 (27.8)
US AGM 31	31	Dual	117	45	207	12.9" (328mm)	6.77" (172mm)	8.66" (220mm)	67 (30.5)
US AGM 12V150	GC12	T11	150	90	323	12.87" (327mm)	7.09" (180mm)	10.79" (274mm)	93 (42.2)
US AGM 12V240	921	Dual	230	145	522	15.03" (382mm)	7.04" (179mm)	14.5" (370mm)	140 (63.5)
US AGM 4D	4D	Dual	246	146	540	20.55" (522mm)	9.45" (240mm)	8.82" (224mm)	143 (65)
US AGM 8D	8D	Dual	308	180	738	20.5" (521mm)	10.6" (268mm)	8.86" (225mm)	169 (77)

All of our Deep Cycle AGM batteries are specifically manufactured for U.S. Battery under our guidelines assuring our customers they are being provided the highest quality AGM batteries available.

# POWER YOU CAN DEPEND ON!

[WWW.USBATTERY.COM](http://WWW.USBATTERY.COM)