

US 12V G24 - Data Sheet

ESSENTIALi[®]

POWERED BY U.S. BATTERY MFG. CO.



Lithium-Ion Battery
12.8 V | 100AH (1.28kWh)
 CELL CHEMISTRY:
Lithium Iron Phosphate (LFP)
 CASE:
ABS
 Dimensions:
10.24" w x 6.61" l x 8.27" h
 BCI GROUP SIZE:
24

FEATURES

- **IP65 rated construction** prevents damage from outside particles and moisture.
- **Mobile App Enabled** integrated into the battery allows users to monitor the State of Charge and pack status from their mobile devices.
- **Scalable** multiple batteries can be used in parallel for increased capacity.
- **Integrated Battery Management System (BMS)** Helps ensure accurate State of Charge (SOC), cell balancing, and fault detection and handling for optimal performance.
- **Wake Button and LED Indicator** enables users to check the State of Charge and pack status.

BATTERY SPECIFICATIONS

| BCI Group Size | Model | Terminal | Terminal Torque | Dimensions (mm)(±2mm) | | | Weight (kg) |
|----------------|------------|-----------|-----------------|-----------------------|-------------|-------------|-------------|
| | | | | Width | Length | Height | |
| 24 | US 12V G24 | M8 insert | 90 IN-LBS | 10.24" (260) | 6.61" (168) | 8.27" (210) | 22.7 (10.3) |

Internal Protection information: See User's Guide www.usbattery.com/essentialowner

ELECTRICAL SPECIFICATIONS

| Voltage | Capacity | Max Continuous Discharge Current | Max 15s Discharge Current | Max 0.2s Discharge Current |
|--------------------|---------------------|----------------------------------|---------------------------|----------------------------|
| 12.8 V | 100 Ah | 100A | 110A | 300A |
| Max Charge Current | Self Discharge Rate | Low Voltage Cutoff | High Voltage Cutoff | |
| 100A | <3%/month | 10V (Cell 2.5V) | 14.8V (Cell 3.7V) | |








OPERATIONAL SPECIFICATIONS

| Discharging | Charging | Storage |
|-------------------------|-----------------------|-----------------------|
| -4°F~131°F (-20°C~55°C) | 32°F~122°F (0°C~50°C) | 50°F~95°F (10°C~35°C) |

SAFETY/REGULATORY INFORMATION

| Certifications | | | |
|----------------|-------------------------|---------------------------|------|
| Transport | Shipping Classification | Cells | Pack |
| UN/DOT 38.3 | UN3480, Class 9 | UL1973, UL9540A, IEC62619 | TBD |






1675 Sampson Avenue
Corona, CA 92879
(800) 695-0945

1895 Tobacco Road
Augusta, GA 30906
(800) 522-0945

717 North Belair Rd.
Evans, GA 30809
(888) 811-0945



Data references within this publication are nominal and should not be considered or construed as maximum or minimum values for specifications or for final design. Data for this product type and model may vary from what is shown in this publication, and U.S. Battery Mfg. Co. makes No warranties, expressed or implied based on the data within this publication.

©2023 U.S. Battery Mfg. Co. All rights reserved. U.S. Battery is not liable for damages that may occur from any information provided in or omitted from this publication, under any circumstances. U.S. Battery Mfg. Co. reserves the right to make changes or adjustments to this publication at any time without notices or obligations.