

# Specification Guide

## **XC**™ **FEATURES:**

**XTREME CAPACITY 2**  
DIAMOND PLATE TECHNOLOGY

**XC** **Fastest** cycle up to full rated capacity.

**XC** **Highest** initial capacity.

**XC** **Highest** total energy delivered over the life of the battery.



### Flooded Lead-Acid Terminal Options



1675 Sampson Ave.  
Corona, CA 92879  
951.371.8090

1895 Tobacco Rd.  
Augusta, Georgia 30906  
706.790.0218

717 North Belair Road  
Evans, Georgia 30809  
706.868.0533

[WWW.USBATTERY.COM](http://WWW.USBATTERY.COM)

AMERICA'S MOST TRUSTED POWER SOURCE SINCE 1926



## FLOODED LEAD-ACID DEEP CYCLE BATTERIES

U.S. Battery Model	AMP Hours (20hr. rate)	AMP Hours (5hr. rate)	MINUTES @ 75 AMPS	MINUTES @ 56 AMPS	MINUTES @ 25 AMPS	Dimensions, Inches (mm)			Cover and Case	Pallet QTY
						Length	Width	Height		
<b>6 VOLT GOLF CAR &amp; MULTI-PURPOSE</b>										
US 1800XC2	208	157	107	151	392	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 2000XC2	220	172	115	164	445	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 2200XC2	232	181	122	175	474	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 125XC2	242	198	140	198	517	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 145XC2	251	213	154	217	562	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48
<b>8 VOLT GOLF CAR &amp; MULTI-PURPOSE</b>										
US 8VGCXC2	155	129	75	110	312	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 8VGCXC2	170	133	82	118	325	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VGCXC2	183	147	95	136	355	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VHATBXC2	205	170	115	164	435	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48
<b>6 VOLT GOLF, SWEEPER/SCRUBBER &amp; MULTI-PURPOSE</b>										
US 250XC2	255	217	159	224	570	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 250HCXC2	280	239	178	250	535	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 305XC2	290	245	182	256	660	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	BLK/BLK	18
US 305XC2	310	261	195	276	715	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US 305HCXC2	340	283	215	304	790	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US L16EXC2	360	270	198	287	795	w/ handles 12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	BLK/BLK	18
US L16XC2	385	297	225	322	865	w/ handles 12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US L16HCXC2	420	323	250	358	965	w/ handles 12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US 1HCXC2	95	-	44	-	165	8 3/4 (222)	6 7/8 (175)	9 (175)	BLK/BLK	72
US 100DINXC2	247	199	135	204	560	9 5/8 (244)	7 1/2 (191)	10 7/8 (276)	RED/RED	48
<b>12 VOLT GOLF, SWEEPER/SCRUBBER &amp; MULTI-PURPOSE</b>										
US 12VEXC2	145	115	62	95	270	w/ handles 14 (355)	7 1/16 (179)	11 3/8 (289)	BLK/BLK	36
US 12VRXC2	155	122	77	110	292	w/ handles 14 (355)	7 1/16 (179)	11 3/8 (289)	RED/RED	36
US 185XC2	185	144	93	133	355	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	BLK/BLK	14
US 185XC2	200	158	106	151	398	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185HCXC2	220	172	117	167	443	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
<b>8 VOLT MARINE</b>										
13-4-1XC2	170	-	116	-	380	21 7/16 (555)	7 1/2 (191)	10 1/2 (257)	RUBBER	24
15-4-1XC2	195	-	133	-	440	24 3/8 (619)	7 7/16 (189)	10 1/2 (257)	RUBBER	16
17-4-1XC2	220	-	147	-	490	27 7/16 (698)	7 7/16 (189)	10 1/2 (257)	RUBBER	16
19-4-1XC2	245	-	162	-	545	26 3/4 (679)	8 7/16 (216)	11 1/8 (282)	RUBBER	16
<b>12 VOLT SWEEPER/SCRUBBER, MARINE &amp; MULTI-PURPOSE</b>										
US 24DCXC2	85	68	38	400	145	10 7/8 (276)	6 3/4 (171)	9 3/8 (238)	RED/RED	72
US 27DCXC2	105	89	54	575	205	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	RED/RED	54
US 31DCXC2	130	99	59	620	225	13 (330)	6 3/4 (171)	9 5/8 (243)	RED/RED	54
<b>12 VOLT MULTI-PURPOSE</b>										
8D-HCXC2	240	177	115	167	470	20 3/4 (527)	11 1/8 (283)	9 7/8 (251)	BLK/BLK	16
<b>2 VOLT RENEWABLE ENERGY</b>										
US REL162VXC2	1100	962	845	1177	2826	w/ handles 12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	RED/RED	18
<b>6 VOLT RENEWABLE ENERGY</b>										
US REGC2HCXC2	242	194	136	193	507	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48
US REL16XC2	401	317	245	348	915	w/ handles 12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	RED/RED	18

## FLOODED LEAD-ACID LOW MAINTENANCE

### STARTING BATTERIES

BCI Group Size	U.S. Battery Model	C.C.A. @ 0°F	C.A. @ 32°F	MINUTES @ 25 AMPS	Dimensions, Inches (mm)			Cover and Case	Pallet QTY
					Length	Width	Height		
<b>6 VOLT AUTOMOTIVE &amp; COMMERCIAL</b>									
2E	2E	600	730	180	19 3/8 (492)	4 1/8 (105)	9 1/8 (232)	RUBBER	60
19L	19L	525	640	110	8 3/16 (208)	6 11/16 (170)	7 7/16 (189)	RUBBER	90
<b>12 VOLT TRUCK, BUS, COMMERCIAL</b>									
17TF	17TF	625	765	150	17 1/16 (433)	6 15/16 (176)	8 (203)	RUBBER	42
<b>12 VOLT MILITARY ORDINANCE</b>									
6TL(mil)	6TMF	750	-	230	11 1/4 (286)	10 1/2 (267)	9 (229)	BLK/BRN	36

## AGM SEALED DEEP CYCLE BATTERIES

U.S. Battery Model	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	TERMINALS	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	Dimensions, Inches (mm)			Cover and Case	Pallet QTY
						Length	Width	Height		
<b>6 VOLT AGM DEEP CYCLE</b>										
US AGM2000	210	177	DUAL	120	460	10.24 (260)	7.09 (180)	10.79 (274)	RED/RED	32
US AGM6V27	215	182	T11	112	500	12.05 (306)	6.61 (168)	8.98 (228)	RED/RED	24
US AGM2224	225	195	F14	142	510	10.2 (260)	7.09 (180)	9.9 (252)	RED/RED	32
US AGM6V260	260	220	F14	156	560	10.2 (260)	7.09 (180)	10.7 (272)	RED/RED	32
US AGM305	340	306	DUAL	240	790	11.61 (295)	7 (178)	14.3 (364)	RED/RED	12
US AGML16	414	360	DUAL	275	984	11.61 (295)	7 (178)	16.66 (423)	RED/RED	12
<b>8 VOLT AGM DEEP CYCLE</b>										
US AGM8V170	180	149	DUAL	120	381	10.2 (260)	7.17 (182)	11.3 (286)	RED/RED	40
<b>12 VOLT AGM DEEP CYCLE</b>										
US AGMU1	35	29	F11	11	45	7.68 (195)	5.12 (130)	7.13 (181)	RED/RED	60
US AGM24	90	82	T6-A	43	175	10.24 (260)	6.61 (168)	8.43 (214)	RED/RED	36
US AGM27	112	98	DUAL	55	220	12.05 (306)	6.61 (168)	9.17 (233)	RED/RED	36
US AGM31	117	96	F12	45	207	12.9 (328)	6.77 (172)	8.66 (220)	RED/RED	30
US AGM12V150	150	133	T11	90	323	12.87 (327)	7.09 (180)	10.79 (274)	RED/RED	24
US AGM12V240	230	203	DUAL	145	522	15.03 (382)	7.04 (179)	14.5 (370)	RED/RED	10
US AGM8D	308	252	F14	180	738	20.5 (521)	10.6 (268)	8.86 (225)	RED/RED	12

## ESSENTIAL Li<sup>®</sup> DEEP CYCLE BATTERIES

BCI Group Size	U.S. Battery Model	Capacity	TERMINALS	Dimensions, Inches (mm)			Weight (kg)	Cover and Case	Pallet QTY
				Length	Width	Height			
<b>12 VOLT LITHIUM-ION DEEP CYCLE</b>									
G24	US 12VG24	100AH	M8 INSERT	10.24 (260)	6.61 (168)	8.27 (210)	22.7 (10.3)	RED/RED	36
<b>24 VOLT LITHIUM-ION DEEP CYCLE</b>									
GC2	US 24VGC2	67AH	M8 INSERT	10.24 (260)	7.09 (180)	11.04 (280)	32.2 (14.6)	RED/RED	48
<b>48 VOLT LITHIUM-ION DEEP CYCLE</b>									
GC2	US 48VGC2	30AH	M8 INSERT	7.68 (195)	5.12 (130)	7.13 (181)	32.2 (14.6)	RED/RED	48
N/A	US 48V105	105AH	M8 INSERT	17.05 (433)	17.46 (443.5)	10.32 (262)	90.7 (41.2)	RED/RED	12