

**SETTING THE INDUSTRY STANDARD**

12 Volt  
US 12VRX



12 Volt  
US 27 DC



- XC** Highest initial capacity.
- XC** Fastest cycle up to full rated capacity.
- XC** Highest total energy delivered over the life of the battery.
- XC** Ultimate compatibility with the wide range of chargers used in the field.
- XC** High charge efficiency designed to meet the new California Energy Commission regulations for combined charger/battery charge efficiency.



12 Volt  
US 31DC

8 Volt  
US 15-4-1

6 Volt  
US 2000



1675 Sampson Ave.  
Corona, CA 92879  
(800) 695-0945

1895 Tobacco Rd.  
Augusta, GA 30906  
(800) 522-0945

717 North Belair Rd.  
Evans, GA 30809  
(888) 811-0945

**WWW.USBATTERY.COM**

# POWER YOU CAN DEPEND ON!

## 6 Volt Marine

Type	20 HR rate	5 HR rate	Min @ 75 Amps	Min @ 25 Amps	Length	Width	Height	Pallet QTY
US 1800 XC2	208	157	107	392	10-1/4 (260mm)	7-1/8 (181mm)	11-1/4 (286mm)	48
US 2000 XC2	220	172	115	445	10-1/4 (260mm)	7-1/8 (181mm)	11-1/4 (286mm)	48
US 2200 XC2	232	181	122	474	10-1/4 (260mm)	7-1/8 (181mm)	11-1/4 (286mm)	48
US 125 XC2	242	198	140	517	10-1/4 (260mm)	7-1/8 (181mm)	11-1/4 (286mm)	48
US 145 XC2	251	213	154	562	10-1/4 (260mm)	7-1/8 (181mm)	11-7/8 (302mm)	48
US 250 XC2	255	217	159	570	11-5/8 (295mm)	7-1/8 (181mm)	11-5/8 (295mm)	36
US 250HC XC2	280	239	178	635	11-5/8 (295mm)	7-1/8 (181mm)	11-5/8 (295mm)	36

## 8 Volt Marine

15-4-1 XC2	195	-	133	440	24-3/8" (619mm)	7-1/16" (189mm)	10-1/2" (267mm)	16
17-4-1 XC2	220	-	147	490	27-1/16" (689mm)	7-1/16" (189mm)	10-1/2" (267mm)	16
19-4-1 XC2	245	-	162	545	26-3/4" (679mm)	8-7/16" (216mm)	11-1/8" (282mm)	16

## 12 Volt Marine

US 12VRX XC2	155	122	77	292	14 (355mm) w/handles	7-1/16" (179mm)	11-3/8" (289mm)	36
US 12VE XC2	145	115	62	270	14 (355mm) w/handles	7-1/16" (179mm)	11-3/8" (289mm)	36
US 24DC XC2	85	68	38	145	10-7/8 (276mm)	6-3/4" (171mm)	9-3/8 (238mm)	54
US 27DC XC2	105	89	54	205	12-3/4" (324mm)	6-3/4" (171mm)	9-3/4" (248mm)	54
US 31DC XC2	130	99	59	225	13" (330mm)	6-3/4" (171mm)	9-5/8 (243mm)	54

## 6 Volt AGM Marine

Type	20 HR rate	5 HR rate	Min of Discharge @75 Amps	Min of Discharge @56 Amps	Min of Discharge @25 Amps	CCA @ 0°F		Length	Width	Height
						-18°C	0°C			
US AGM 2000	213	182	124	177	475	710	855	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)
US AGM 250	260	212	149	213	572	745	895	11.61" (295mm)	7.09" (180mm)	11.73" (298mm)
US AGM 305	312	273	208	291	736	720	865	11.61" (295mm)	7.09" (180mm)	14.41" (366mm)
US AGM L16	390	326	255	358	915	730	875	11.61" (295mm)	7.09" (180mm)	16.85" (428mm)

## 12 Volt AGM Marine

US AGM 27	99	82	52	73	185	750	900	12.05" (306mm)	6.61" (168mm)	9.06" (230mm)
US AGM 31	100	85	52	73	190	800	960	13.7" (348mm)	6.85" (174mm)	9.37" (238mm)
US AGM 185	234	191	125	182	518	775	930	15.24" (387mm)	7.09" (180mm)	14.49" (368mm)

# AGM Series

## NEW LOOK SAME QUALITY BATTERIES!

- Sealed Low Maintenance
- Produces very little gassing.
- Rarely effected by freezing temperatures.
- Rigid plate construction and mounting to withstand shock and vibration.



6 Volt  
US AGM 2000

12 Volt  
US AGM 185

12 Volt  
US AGM 31

[WWW.USBATTERY.COM](http://WWW.USBATTERY.COM)

