

Specification Guide



FEATURES:

-  **Highest** initial capacity.
-  **Highest** total energy delivered over the life of the battery.
-  **Fastest** cycle up to full rated capacity.



Terminal Options



1675 Sampson Ave.
Corona, CA 92879
951. 371.8090

1895 Tobacco Rd.
Augusta, Georgia 30906
706.790.0218

717 North Belair Road
Evans, Georgia 30809
706.868.0533



WWW.USBATTERY.COM

AMERICA'S MOST TRUSTED POWER SOURCE SINCE 1926

DEEP CYCLE BATTERIES

US BATTERY MODEL	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	M.C.A. @ 32° F	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
						LENGTH	WIDTH	HEIGHT		

6 VOLT GOLF CAR & MULTI PURPOSE

US 1800XC2	208	157	-	107	392	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 2000XC2	220	172	-	115	445	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 2200XC2	232	181	-	122	474	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 125XC2	242	198	-	140	517	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 145XC2	251	213	-	154	562	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48

8 VOLT GOLF CAR & MULTI PURPOSE

US 8VGCXC2	155	129	110	75	312	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 8VGCXC2	170	133	118	82	325	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VGCXCXC2	183	147	136	95	365	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VHATBXC2	205	170	164	115	435	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48

6 VOLT GOLF, SWEEPER/SCRUBBER & MULTI PURPOSE

US 250XC2	255	217	-	159	570	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 250HCXC2	280	239	-	178	635	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 305XC2	290	245	-	182	660	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	BLK/BLK	18
US 305XC2	310	261	-	195	715	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US 305HCXC2	340	283	-	215	790	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US L16EXC2	360	270	-	198	795	12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	BLK/BLK	18
US L16XC2	385	297	-	225	865	12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US L16HCXC2	420	323	-	250	965	12 7/16 (315)	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US 1 HCXC2	95	-	-	44	165	8 3/4 (222)	6 7/8 (175)	9 (175)	BLK/BLK	72
US 100DINXC2	247	199	-	135	560	9 5/8 (244)	7 1/2 (191)	10 7/8 (276)	RED/RED	48

12 VOLT GOLF, SWEEPER/SCRUBBER & MULTI PURPOSE

US 12VRXXC2	155	122	-	77	292	14 (355)	7 1/16 (179)	11 3/8 (289)	RED/RED	36
US 12VEXC2	145	115	-	62	270	14 (355)	7 1/16 (179)	11 3/8 (289)	BLK/BLK	36
US 185XC2	200	158	-	106	398	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185HCXC2	220	172	-	117	443	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185EXC2	185	144	-	93	355	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	BLK/BLK	14

8 VOLT MARINE

15-4-1 XC2	195	-	-	133	440	24 3/8 (619)	7 7/16 (189)	10 1/2 (267)	RUBBER	16
17-4-1 XC2	220	-	-	147	490	27 7/16 (698)	7 7/16 (189)	10 1/2 (267)	RUBBER	16
19-4-1 XC2	245	-	-	162	545	26 3/4 (679)	8 7/16 (216)	11 1/8 (282)	RUBBER	16

12 VOLT SWEEPER/SCRUBBER, MARINE & MULTI PURPOSE

US 24 DCXC2	85	68	400	38	145	10 7/8 (276)	6 3/4 (171)	9 3/8 (238)	RED/RED	72
US 27 DCXC2	105	89	575	54	205	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	RED/RED	54
US 31 DCXC2	130	99	620	59	225	13 (330)	6 3/4 (171)	9 5/8 (243)	RED/RED	54

12 VOLT MULTI PURPOSE

8D-HCXC2	240	177	-	115	470	20 3/4 (527)	11 1/8 (283)	9 7/8 (251)	BLK/BLK	16
----------	-----	-----	---	-----	-----	--------------	--------------	-------------	---------	----

6 VOLT RENEWABLE ENERGY

US RE L16XC2	401	317	-	245	915	11 7/8 (302)	7 7/8 (181)	16 3/4 (425)	GRN/GRN	18
US REGC2HXC2	242	194	-	136	507	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	GRN/GRN	48

2 VOLT RENEWABLE ENERGY

US RE L162VXC2	1100	962	-	845	2826	11 7/8 (302)	7 7/8 (181)	16 3/4 (425)	GRN/GRN	18
----------------	------	-----	---	-----	------	--------------	-------------	--------------	---------	----

LOW MAINTENANCE STARTING BATTERIES

BCI GROUP SIZE	US BATTERY MODEL	C.C.A. @ 0° F	C.A. @ 32° F	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
					LENGTH	WIDTH	HEIGHT		

6 VOLT AUTOMOTIVE & COMMERCIAL

2E	2E	600	730	180	19 3/8 (492)	4 1/8 (105)	9 1/8 (232)	RUBBER	60
19L	19L	525	640	110	8 3/16 (208)	6 11/16 (170)	7 7/16 (189)	RUBBER	90

12 VOLT TRUCK - BUS - COMMERCIAL

17TF	17TF	625	765	150	17 1/16 (433)	6 15/16 (176)	8 (203)	RUBBER	42
------	------	-----	-----	-----	---------------	---------------	---------	--------	----

12 VOLT MILITARY ORDINANCE

6TL(mil)	6TMF	750	----	230	11 1/4 (286)	10 1/2 (267)	9 (229)	BLK/BRN	36
----------	------	-----	------	-----	--------------	--------------	---------	---------	----

12 VOLT GAS GOLF CAR & AUTOMOTIVE

53	53K-30	360	440	65	12 3/4 (324)	4 5/8 (117)	8 15/16 (227)	BLK/BLK	90
----	--------	-----	-----	----	--------------	-------------	---------------	---------	----



6, 8, & 12 Volt AGM - Sealed Non-spillable Batteries

US BATTERY MODEL	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	TERMINALS	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
						LENGTH	WIDTH	HEIGHT		

6 VOLT AGM DEEP CYCLE

US AGM 2000	210	177	DUAL	120	460	10.24 (260)	7.09 (180)	10.79 (274)	RED/RED	32
US AGM 6V27	215	182	T11	112	500	12.05 (306)	6.61 (168)	8.98 (228)	RED/RED	24
US AGM 2224	224	190	T11	135	490	10.24 (260)	7.09 (180)	9.96 (253)	RED/RED	32
US AGM 6V260	280	245	T11	180	630	10.24 (260)	7.09 (180)	10.35 (263)	RED/RED	32
US AGM 305	350	307	DUAL	240	820	11.61 (295)	7.09 (180)	14.49 (368)	RED/RED	12
US AGM L16	400	336	DUAL	265	925	11.61 (295)	7.09 (180)	16.85 (428)	RED/RED	12

8 VOLT AGM DEEP CYCLE

US AGM 8V170	180	149	DUAL	120	381	10.2 (260)	7.17 (182)	11.3 (286)	RED/RED	40
--------------	-----	-----	------	-----	-----	------------	------------	------------	---------	----

12 VOLT AGM DEEP CYCLE

US AGM U1	35	29	F7	11	45	7.68 (195)	5.12 (130)	7.13 (181)	RED/RED	60
US AGM 24	90	82	T6-A	43	175	10.24 (260)	6.61 (168)	8.43 (214)	RED/RED	36
US AGM 27	108	98	DUAL	55	220	12.05 (306)	6.61 (168)	9.17 (233)	RED/RED	36
US AGM 31	117	96	F12	45	207	12.9 (328)	6.77 (172)	8.66 (220)	RED/RED	30
US AGM 12V140	144	132	T11	88	321	16.1 (408)	6.97 (177)	8.86 (225)	RED/RED	24
US AGM 12V150	150	133	T11	90	323	12.87 (327)	7.09 (180)	10.79 (274)	RED/RED	24
US AGM 12V240	245	203	DUAL	145	535	15.24 (387)	7.09 (180)	14.49 (368)	RED/RED	10
US AGM 8D	308	252	F14	180	738	20.5 (521)	10.6 (268)	8.86 (225)	RED/RED	12