

Specification Guide

XC™ **FEATURES:**

XTREME CAPACITY 2
DIAMOND PLATE TECHNOLOGY

XC Fastest cycle up to full rated capacity.

XC Highest initial capacity.

XC Highest total energy delivered over the life of the battery.



Flooded Lead-Acid Terminal Options



1675 Sampson Ave.
Corona, CA 92879
951.371.8090

1895 Tobacco Rd.
Augusta, Georgia 30906
706.790.0218

717 North Belair Road
Evans, Georgia 30809
706.868.0533



WWW.USBATTERY.COM



AMERICA'S MOST TRUSTED POWER SOURCE SINCE 1926

FLOODED LEAD-ACID DEEP CYCLE BATTERIES										
U.S. Battery Model	AMP Hours (20hr. rate)	AMP Hours (5hr. rate)	MINUTES @ 75 AMPS	MINUTES @ 56 AMPS	MINUTES @ 25 AMPS	Dimensions, Inches (mm)			Cover and Case	Pal-let QTY
						Length	Width	Height		
6 VOLT GOLF CAR & MULTI-PURPOSE										
US 1800XC2	208	157	107	151	392	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 2000XC2	220	172	115	164	445	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 2200XC2	232	181	122	175	474	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 125XC2	242	198	140	198	517	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 145XC2	251	213	154	217	562	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48
8 VOLT GOLF CAR & MULTI-PURPOSE										
US 8VGCXC2	155	129	75	110	312	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 8VGCXC2	170	133	82	118	325	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VGCXC2	183	147	95	136	355	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VHATBXC2	205	170	115	164	435	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48
6 VOLT GOLF, SWEEPER/SCRUBBER & MULTI-PURPOSE										
US 250XC2	255	217	159	224	570	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 250HCXC2	280	239	178	250	535	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 305EXC2	290	245	182	256	660	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	BLK/BLK	18
US 305XC2	310	261	195	276	715	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US 305HCXC2	340	283	215	304	790	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US L16EXC2	360	270	198	287	795	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	BLK/BLK	18
US L16XC2	385	297	225	322	865	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US L16HCXC2	420	323	250	358	965	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US 1HCXC2	95	-	44	-	165	8 3/4 (222)	6 7/8 (175)	9 (175)	BLK/BLK	72
US 100DINXC2	247	199	135	204	560	9 5/8 (244)	7 1/2 (191)	10 7/8 (276)	RED/RED	48
12 VOLT GOLF, SWEEPER/SCRUBBER & MULTI-PURPOSE										
US 12VEXC2	145	115	62	95	270	14 (355) w/ handles	7 1/16 (179)	11 3/8 (289)	BLK/BLK	36
US 12VRXXC2	155	122	77	110	292	14 (355) w/ handles	7 1/16 (179)	11 3/8 (289)	RED/RED	36
US 185EXC2	185	144	93	133	355	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	BLK/BLK	14
US 185XC2	200	158	106	151	398	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185HCXC2	220	172	117	167	443	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
8 VOLT MARINE										
13-4-1XC2	170	-	116	-	380	21 7/16 (555)	7 1/2 (191)	10 1/2 (257)	RUBBER	24
15-4-1XC2	195	-	133	-	440	24 3/8 (619)	7 7/16 (189)	10 1/2 (257)	RUBBER	16
17-4-1XC2	220	-	147	-	490	27 7/16 (698)	7 7/16 (189)	10 1/2 (257)	RUBBER	16
19-4-1XC2	245	-	162	-	545	26 3/4 (679)	8 7/16 (216)	11 1/8 (282)	RUBBER	16
12 VOLT SWEEPER/SCRUBBER, MARINE & MULTI-PURPOSE										
US 24DCXC2	85	68	38	400	145	10 7/8 (276)	6 3/4 (171)	9 3/8 (238)	RED/RED	72
US 27DCXC2	105	89	54	575	205	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	RED/RED	54
US 31DCXC2	130	99	59	620	225	13 (330)	6 3/4 (171)	9 5/8 (243)	RED/RED	54
2 VOLT RENEWABLE ENERGY										
US REL162VXC2	1100	962	845	1177	2826	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
6 VOLT RENEWABLE ENERGY										
US REGC2HXC2	242	194	136	193	507	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48
US REL16XC2	401	317	245	348	915	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18

FLOODED LEAD-ACID LOW MAINTENANCE STARTING BATTERIES										
BCI Group Size	U.S. Battery Model	C.C.A. @ 0°F	C.A. @ 32°F	MINUTES @ 25 AMPS	Dimensions, Inches (mm)			Cover and Case	Pallet QTY	
					Length	Width	Height			
6 VOLT AUTOMOTIVE & COMMERCIAL										
2E	2E	600	730	180	19 3/8 (492)	4 1/8 (105)	9 1/8 (232)	RUBBER	60	
19L	19L	525	640	110	8 3/16 (208)	6 11/16 (170)	7 7/16 (189)	RUBBER	90	
12 VOLT TRUCK, BUS, COMMERCIAL										
17TF	17TF	625	765	150	17 1/16 (433)	6 15/16 (176)	8 (203)	RUBBER	42	
12 VOLT MILITARY ORDINANCE										
6TL(mil)	6TMF	750	-	230	11 1/4 (286)	10 1/2 (267)	9 (229)	BLK/BRN	36	
AGM SEALED DEEP CYCLE BATTERIES										
U.S. Battery Model	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	TERMINALS	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	Dimensions, Inches (mm)			Cover and Case	Pallet QTY
						Length	Width	Height		
6 VOLT AGM DEEP CYCLE										
US AGM2000	210	177	DUAL	120	460	10.24 (260)	7.09 (180)	10.79 (274)	RED/RED	32
US AGM6V27	215	182	T11	112	500	12.05 (306)	6.61 (168)	8.98 (228)	RED/RED	24
US AGM2224	224	190	F14	135	490	10.2 (260)	7.09 (180)	9.9 (252)	RED/RED	40
US AGM6V260	260	220	F14	156	560	10.2 (260)	7.09 (180)	10.7 (272)	RED/RED	32
US AGM305	340	306	DUAL	240	790	11.61 (295)	7 (178)	14.3 (364)	RED/RED	30
US AGML16	414	360	DUAL	275	984	11.61 (295)	7 (178)	16.66 (423)	RED/RED	15
8 VOLT AGM DEEP CYCLE										
US AGM8V170	180	149	DUAL	120	381	10.2 (260)	7.17 (182)	11.3 (286)	RED/RED	40
12 VOLT AGM DEEP CYCLE										
US AGMU1	35	29	F11	11	45	7.68 (195)	5.12 (130)	7.13 (181)	RED/RED	60
US AGM24	90	82	T6-A	43	175	10.24 (260)	6.61 (168)	8.43 (214)	RED/RED	48
US AGM27	112	98	DUAL	55	220	12.05 (306)	6.61 (168)	9.17 (233)	RED/RED	36
US AGM31	117	96	F12	45	207	12.9 (328)	6.77 (172)	8.66 (220)	RED/RED	30
USAGM12V150	150	133	T11	90	323	12.87 (327)	7.09 (180)	10.79 (274)	RED/RED	24
USAGM12V240	230	203	DUAL	145	522	15.03 (382)	7.04 (179)	14.5 (370)	RED/RED	10
US AGM4D	246	206	F10	146	540	20.55 (522)	9.45 (240)	8.82 (224)	RED/RED	12
US AGM8D	308	252	F14	180	738	20.5 (521)	10.6 (268)	8.86 (225)	RED/RED	12
ESSENTIAL Li[®] DEEP CYCLE BATTERIES										
BCI Group Size	U.S. Battery Model	Capacity	TERMINALS	Dimensions, Inches (mm)			Weight (kg)	Cover and Case	Pallet QTY	
				Length	Width	Height				
12 VOLT LITHIUM-ION DEEP CYCLE										
G24	US 12VG24	100AH	M8 INSERT	10.24 (260)	6.61 (168)	8.27 (210)	22.7 (10.3)	RED/RED	45	
24 VOLT LITHIUM-ION DEEP CYCLE										
GC2	US 24VGC2	67AH	M8 INSERT	10.24 (260)	7.09 (180)	11.04 (280)	32.2 (14.6)	RED/RED	55	
48 VOLT LITHIUM-ION DEEP CYCLE										
GC2	US 48VGC2	30AH	M8 INSERT	7.68 (195)	5.12 (130)	7.13 (181)	32.2 (14.6)	RED/RED	55	
N/A	US 48V105	105AH	M8 INSERT	17.05 (433)	17.46 (443.5)	10.32 (262)	90.7 (41.2)	RED/RED	25	